

Claims

1. A covering arrangement for a building, the arrangement  
having parallel elongate supports and, arranged on the  
5 supports, covering parts which

- a) comprise a core and, connected thereto, upper and  
lower planar covering elements in the manner of a  
sandwich,
- 10 b) have an elongate, striplike form,
- c) in the installed position are arranged transversely to  
the supports and extend at least from one support to a  
15 neighbouring support,

wherein

- d) a longitudinal border region (30) of a covering  
20 part (16) has a connecting device (68) and the  
opposite longitudinal border region (34) of a  
neighbouring covering part (16) has a connecting  
device (70) complementary thereto, by means of which  
the two covering parts (16) are firmly connected to  
25 each other.

2. A covering arrangement as claimed in claim 1, said  
arrangement being a roof (10) and said supports being  
rafters (14) of the roof (10).

30

3. A covering part for use in a covering arrangement as  
claimed in one of claims 1 and 2, which

- a) comprises a core and, connected thereto, upper and  
35 lower planar covering elements in the manner of a  
sandwich and

b) has an elongate, striplike form,

wherein

5 c) its one longitudinal border region (30) has a  
connecting device (68) and its opposite longitudinal  
border region (34) has a connecting device (70)  
complementary thereto, such that the covering  
part (16) can be firmly connected to an identical  
10 covering part (16) at, in the installed position,  
mutually facing longitudinal border regions (30, 34).

4. A covering part as claimed in claim 3, wherein the  
connecting devices (68, 70) comprise at least one catch  
15 projection (78) and a catch recess (72, 74, 76)  
complementary thereto.

5. A covering part as claimed in one of claims 2 and 3,  
wherein the two connecting devices (68, 70) in the  
20 installed position cooperate in the manner of a hinge, the  
pivot axis running substantially parallel to the  
longitudinal axis of the covering part (16).

6. A covering part as claimed in one of claims 2 to 5,  
25 wherein at least one of the connecting devices (68, 70) is  
integrated into a stiffening member (32, 36) arranged in  
the region of the corresponding longitudinal border region  
(30, 34) of said covering part.

30 7. A covering part as claimed in one of claims 2 to 6,  
wherein the connecting devices (68, 70) each extend over  
its entire length.

8. A covering part as claimed in one of claims 2 to 7,  
35 wherein the connecting devices (68, 70) are designed in  
such a way that, in the installed position, the mutually

facing longitudinal border regions (30, 34) of neighbouring covering parts (16) at least regionally overlap.

9. A covering part as claimed in claim 8, wherein one of  
5 its longitudinal borders (34) is drawn down.

10. A covering part as claimed in one of claims 8 and 9,  
wherein one of its longitudinal borders (30) is drawn up.

10 11. A covering part as claimed in one of claims 2 to 10,  
wherein at least one of the connecting devices (68) has a  
plurality of connecting positions (72, 74, 76), such that  
the relative position of the covering part (16) with  
respect to a neighbouring covering part (16) can be varied.

15

12. A covering part as claimed in one of claims 2 to 11,  
wherein the connecting device (68) can be connected to a  
snow fence (102) and/or a ladder and/or steps and/or a  
flashing.